

JSR 354 Money & Currency TCK User Guide

Anatole Tresch

Table of Contents

1. Introduction to Java Money	1
1.1. Overview	1
1.2. Downloading and Installing	2
1.3. Main Design Decisions	3
1.4. Component Loading and Bootstrapping	3
2. The org.javamoney.tck.JSR354TestConfiguration Interface	4
2.1. Checking the Results	7
2.2. Contacts	19

Copyright (c) 2012, 2013, Werner Keil, Credit Suisse (Anatole Tresch). Licensed under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at <http://www.apache.org/licenses/LICENSE-2.0> Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License. Contributors: Anatole Tresch - initial version.

JSR 354 *Java Money* defines the Java API for managing monetary amounts and currencies in Java. As other JSRs beside the reference implementations also other third parties can provide their implementations. This document will describe how this technical compatibility kit (TCK) can be configured and used to determine the compatibility of an implementation with the specification and reference implementation.

This document

This is a user guide that describes all relevant aspects of the JSR 354 Java Money TCK, for using this TCK with any reference implementation.

1. Introduction to Java Money

NOTE | You may also read the JSR 354 API specification available [here](#).

1.1. Overview

The technical compatibility kit (TCK) of a JSR ensures that implementations of a JSR implement the specification correctly and help to ensure also behavioural interoperability between different implementations. So the TCK for JSR 354 Money and Currency ensures exactly this for implementations of the Money & Currency JSR. The TCK hereby is open sourced under the Apache 2 licence. Nevertheless we would be highly interested to keep track of implementation of this JSR. So if you are planning or even writing on an implementation of this JSR, drop a mail to the JSR's [mailing list](#) on [java.net](#) or the JSR's [spec lead](#).

1.2. Downloading and Installing

Basically the JSR 354 API as well as the TCK and its dependencies are available as maven artifacts. Hereby JSR 354 defines a Java 7 based API, which comprises almost all functionality that but also comes with a Java 8 API, which adds Java 8 related additional features (default methods that makes developer's life easier):

- `javax.money:money-api:1.0:jar` contains the full Java 8 based API
- `javax.money:money-api-bp:1.0:jar` contains the Java SE pre8 compatible API.
- `org.javamoney:moneta:<version>:jar` contains the Java 8 compatible reference implementation (RI)
- `org.javamoney:moneta-bp:<version>:jar` contains the Java SE pre8 compatible reference implementation (RI)
- `org.javamoney:money-tck:<version>:jar` contains the technological compatibility kit (TCK), built against the Java 7 API, which is compatible with the Java 8 version.

Summarizing you should add the following dependencies:

```
<dependency>
  <groupId>org.javamoney</groupId>
  <artifactId>money-tck</artifactId>
  <version>1.0</version> <!-- or newer, if available. -->
</dependency>
<dependency>
  <groupId>org.testng</groupId>
  <artifactId>testng</artifactId>
  <version>6.8.5</version>
</dependency>
<dependency>
  <groupId>${impl.groupId}</groupId>
  <artifactId>${impl.artifactId}</artifactId>
  <type>${impl.packageType}</type>
  <version>${impl.version}</version>
</dependency>

<!-- Not necessary, if your implementation has this dependency in compile scope... -->
<dependency>
  <groupId>javax.money</groupId>
  <artifactId>money-api</artifactId>
  <!-- Java 7: artifactId>money-api-bp</artifactId -->
  <type>jar</type>
  <version>1.0</version>
</dependency>
```

Also we have added [example maven project for Java 8](#) and [example maven project for Java 7](#) that can be used as a starting point. All you have to do is clone it from GitHub and exchange the implementation under test with your own.

1.3. Main Design Decisions

Basically the TCK is a set of tests executed with TestNG. Basic reason for using TestNG is that this library also is used in OpenJDK. Additionally in case of tests are failing you should see a detailed message and a reference to the according section in the specification. The audit of the test coverage can be found [here](#).

1.4. Component Loading and Bootstrapping

The TCK itself is built as a self-executable TestNG program. To execute the TCK basically two prerequisites are necessary: . you must have all required libraries on the classpath. This includes the JSR's API, your implementation under test, the TCK and TestNG, including all required dependencies. . You have to provide a small class, implementing the `org.javamoney.tck.JSR354TestConfiguration`

interface and register it with the JDK's `java.util.ServiceLoader` mechanism.

This can be achieved in different ways:

- The most easiest way to run the tests is to create a small maven project, where you add the JSR 354 API, your implementation and the TCK as dependency. The only thing to be done is executing the test suite by running `org.javamoney.tck.TCKRunner.main`, e.g. from your IDE.
- Or you can execute the TCK by starting it on the console:

Running the TCK

```
java -cp ... org.javamoney.tck.TCKRunner
```

Hereby the TCK allows to set additional system properties:

- `outputDir` allows to set the output directory used by Test NG.
- `reportFile` allows to define the file, which contains the TCK's test result summary (your TCK report).
- `verbose` allows to enable TestNG to log in verbose mode.

So you can also run the TCK with the options above:

Running the TCK with options

```
java -cp ... -Dverbose=true -DoutputDir=c:/temp -DreportFile=./tck-report.txt  
org.javamoney.tck.TCKRunner
```

2. The `org.javamoney.tck.JSR354TestConfiguration` Interface

As mentioned before it is required that you implement an instance of the TCK's `org.javamoney.tck.JSR354TestConfiguration` interface:

Interface JSR354TestConfiguration

```
/**
 * Libraries that implement this JSR and want to be tested with this TCK must implement
 this
 * interface and register it using the {@link ServiceLoader}.
 *
 * @author Anatole Tresch
 */
public interface JSR354TestConfiguration{

    /**
     * Return a collection with all {@link MonetaryAmount} classes that are implemented.
 The list
     * must not be empty and should contain <b>every</b> amount class implemented.<br/>
     * This enables the TCK to check in addition to the basic implementation compliance,
 if
     * according {@link MonetaryAmountFactoryProviderSpi} are registered/available
 correctly.
     *
     * @return a collection with all implemented amount classes, not null.
     */
    Collection<Class> getAmountClasses();

    /**
     * List a collection of {@link CurrencyUnit} implementation.<br/>
     * This enables the TCK to check the basic implementation compliance,
     *
     * @return
     */
    Collection<Class> getCurrencyClasses();

    /**
     * This method allows to let instances of MonetaryOperator to be tested for
 requirements and recommendations.
     *
     * @return the list of operators to be checked, not null. It is allowed to return an
 empty list here, which will
     * disable TCK tests for MonetaryOperator instances.
     */
    Collection<MonetaryOperator> getMonetaryOperators4Test();

}
```

Following find the example implementation that is used for testing the *moneta* reference implementation:

TestSetup for the Moneta Reference Implementation

```
/**
 * Created by Anatole on 14.06.2014.
 */
public final class MonetaTCKSetup implements JSR354TestConfiguration{

    @Override
    public Collection<Class> getAmountClasses() {
        return Arrays
            .asList(new Class[]{FastMoney.class, FastMoney.class});
    }

    @Override
    public Collection<Class> getCurrencyClasses() {
        try{
            return Arrays
                .asList(new Class[] { Class.forName(
"org.javamoney.moneta.internal.JDKCurrencyAdapter")});
        }
        catch(ClassNotFoundException e){
            e.printStackTrace();
            throw new RuntimeException("Currency class not loadable:
org.javamoney.moneta.internal.JDKCurrencyAdapter");
        }
    }

    @Override
    public Collection<MonetaryOperator> getMonetaryOperators4Test(){
        List<MonetaryOperator> ops = new ArrayList<>();
        ops.add(MonetaryFunctions.majorPart());
        ops.add(MonetaryFunctions.minorPart());
        ops.add(MonetaryFunctions.percent(BigDecimal.ONE));
        ops.add(MonetaryFunctions.percent(3.5));
        ops.add(MonetaryFunctions.permil(10.3));
        ops.add(MonetaryFunctions.permil(BigDecimal.ONE));
        ops.add(MonetaryFunctions.permil(10.5, MathContext.DECIMAL32));
        ops.add(MonetaryFunctions.reciprocal());
        ops.add(Monetary.getRounding());
        ops.add(MonetaryConversions.getConversion("EUR"));
        return ops;
    }
}
```

You must register your implementation with the `java.util.ServiceLoader`. This is done by adding the following configuration file to your classpath:

Configuring the TCK Test Setup

```
META-INF
  \_ services
    \_ org.javamoney.tck.JSR354TestConfiguration
```

The *org.javamoney.tck.JSR354TestConfiguration* file should contain exactly one line with the fully qualified class name of your implementation provided:

Contents of the org.javamoney.tck.JSR354TestConfiguration file

```
com.mycomp.mymoney-lib.TCKSetup
```

2.1. Checking the Results

Test execution is logged verbosely on the runtime console. Additionally after TCK execution you should find a folder **tck-results** within your working directory, containing the TestNG result in html (index.html) or xml format. Find following an example output from testing the reference implementation:

Example TCK Console Output

... (Basic Trace Output)

```
=====
JSR354-TCK - Commons, version 1.0
Total tests run: 219, Failures: 0, Skips: 0
=====
```

```
*****
**** JSR 354 - Money & Currency, Technical Compatibility Kit, version 1.0
*****
```

Executed on Sun Aug 24 00:38:44 CEST 2014

```
[SUCCESS] 4.2.1 Ensure registered CurrencyUnit classes are
Comparable.(ModellingCurrenciesTest#testCurrencyClassesComparable)
[SUCCESS] 4.2.1 Ensure registered CurrencyUnit classes implement
hashCode.(ModellingCurrenciesTest#testCurrencyClassesEqualsHashCode)
[SUCCESS] 4.2.1 Test currencies provided have correct ISO 3-letter currency
codes.(ModellingCurrenciesTest#testEnforce3LetterCode4ISO)
[SUCCESS] 4.2.1 Ensure TCK has CurrencyUnit classes
configured.(ModellingCurrenciesTest#testEnsureCurrencyUnit)
[SUCCESS] 4.2.1 Test currencies provided equal at least currencies from
java.util.Currency.(ModellingCurrenciesTest#testEqualISOCurrencies)
[SUCCESS] 4.2.1 Test currencies provided have correct default fraction digits and numeric
code.(ModellingCurrenciesTest#testISOCodes)
[SUCCESS] 4.2.1 Ensure registered CurrencyUnit classes implement
equals.(ModellingCurrenciesTest#testImplementsEquals)
[SUCCESS] 4.2.1 Ensure registered CurrencyUnit classes are
serializable.(ModellingCurrenciesTest#testImplementsSerializable)
[SUCCESS] 4.2.1 Ensure registered CurrencyUnit classes are
immutable.(ModellingCurrenciesTest#testIsImmutable)
[SUCCESS] 4.2.2 For each amount class, test
absolute().(ModellingMonetaryTest#testAbsolute)
[SUCCESS] 4.2.2 For each amount class, check m1.add(m2), m1, m2 = mixed
fractions.(ModellingMonetaryTest#testAddMixedFractions)
[SUCCESS] 4.2.2 For each amount class, check m1.add(m2), m1, m2 = mixed
ints.(ModellingMonetaryTest#testAddMixedIntegers)
[SUCCESS] 4.2.2 For each amount class, check m1.add(m2), m1 < 0,
m2 < 0.(ModellingMonetaryTest#testAddNegativeIntegers)
[SUCCESS] 4.2.2 For each amount class, check m1.add(m2), m2 is
fraction.(ModellingMonetaryTest#testAddPositiveFractions)
[SUCCESS] 4.2.2 For each amount class, check m1.add(m2), m1 > 0,
m2 > 0.(ModellingMonetaryTest#testAddPositiveIntegers)
[SUCCESS] 4.2.2 For each amount class, ensure ArithmeticException is thrown when adding
exceeding values.(ModellingMonetaryTest#testAdd_ExceedsCapabilities)
```

[SUCCESS] 4.2.2 For each amount class, ensure currency compatibility is working.(ModellingMonetaryTest#testAdd_IncompatibleCurrencies)

[SUCCESS] 4.2.2 For each amount class, ensure NullPointerException is thrown when calling m.add(null).(ModellingMonetaryTest#testAdd_Null)

[SUCCESS] 4.2.2 For each amount class, ensure m2 = m1.add(0) -> m1==m2.(ModellingMonetaryTest#testAdd_Zero)

[SUCCESS] 4.2.2 Ensure amount can be created with all default currencies.(ModellingMonetaryTest#testCurrencyCode)

[SUCCESS] 4.2.2 For each amount class, ensure correct division.(ModellingMonetaryTest#testDivide)

[SUCCESS] 4.2.2 For each amount class, ensure correct divideAndRemainder().(ModellingMonetaryTest#testDivideAndRemainder)

[SUCCESS] 4.2.2 For each amount class, ensure divideAndRemainder(null) throws a NullPointerException.(ModellingMonetaryTest#testDivideAndRemainderNull)

[SUCCESS] 4.2.2 For each amount class, ensure divideAndRemainder(1) returns same instance.(ModellingMonetaryTest#testDivideAndRemainderOne)

[SUCCESS] 4.2.2 For each amount class, ensure correct divideAndRemainderZero().(ModellingMonetaryTest#testDivideAndRemainderZero)

[SUCCESS] 4.2.2 For each amount class, ensure divide by null throws NullPointerException.(ModellingMonetaryTest#testDivideNull)

[SUCCESS] 4.2.2 For each amount class, ensure divide 1 returns same instance.(ModellingMonetaryTest#testDivideOne)

[SUCCESS] 4.2.2 For each amount class, ensure correct division with int values.(ModellingMonetaryTest#testDivideToIntegralValue)

[SUCCESS] 4.2.2 For each amount class, ensure divide(0) throws ArithmeticException.(ModellingMonetaryTest#testDivideZero)

[SUCCESS] 4.2.2 Ensure Monetary.getAmountTypes() is not null and not empty.(ModellingMonetaryTest#testEnsureMonetaryAmount)

[SUCCESS] 4.2.2 Ensure amounts created return correct getMonetaryContext().(ModellingMonetaryTest#testGetMonetaryContext)

[SUCCESS] 4.2.2 Ensure amounts created return correct getNumber().(ModellingMonetaryTest#testGetNumber)

[SUCCESS] 4.2.2 For each amount class, test iis immutable.(ModellingMonetaryTest#testImmutable)

[SUCCESS] 4.2.2 For each amount class, test is Comparable.(ModellingMonetaryTest#testImplementComparable)

[SUCCESS] 4.2.2 For each amount class, test implements equals().(ModellingMonetaryTest#testImplementsEquals)

[SUCCESS] 4.2.2 For each amount class, test implements hashCode().(ModellingMonetaryTest#testImplementsHashCode)

[SUCCESS] 4.2.2 For each amount class, test isNegative().(ModellingMonetaryTest#testIsNegative)

[SUCCESS] 4.2.2 For each amount class, test isNegativeOrZero().(ModellingMonetaryTest#testIsNegativeOrZero)

[SUCCESS] 4.2.2 For each amount class, test isPositive().(ModellingMonetaryTest#testIsPositive)

[SUCCESS] 4.2.2 For each amount class, test isPositiveOrZero().(ModellingMonetaryTest#testIsPositiveOrZero)

[SUCCESS] 4.2.2 For each amount class, test isZero().(ModellingMonetaryTest#testIsZero)

[SUCCESS] 4.2.2 For each amount class, test isZero(), advanced.(ModellingMonetaryTest#testIsZeroAdvanced)

[SUCCESS] 4.2.2 For each amount class, access factory and create amounts.(ModellingMonetaryTest#testMonetaryAmountFactories)

[SUCCESS] 4.2.2 For each amount class, check multiple instances are not equal.(ModellingMonetaryTest#testMonetaryAmountFactories_CreateWithCurrencies)

[SUCCESS] 4.2.2 For each amount class, check new amounts with explicit MonetaryContext.(ModellingMonetaryTest#testMonetaryAmountFactories_CreateWithMonetaryContext)

[SUCCESS] 4.2.2 For each amount class, check new amounts are not equal for different currencies and contexts.(ModellingMonetaryTest#testMonetaryAmountFactories_CreateWithMonetaryContextNumberAndCurrency)

[SUCCESS] 4.2.2 For each amount class, access factory and create amounts, ensure amounts are equal if they should.(ModellingMonetaryTest#testMonetaryAmountFactories_InstancesMustBeEqual)

[SUCCESS] 4.2.2 For each amount class, check new amounts are not equal.(ModellingMonetaryTest#testMonetaryAmountFactories_InstancesMustBeNotEqual)

[SUCCESS] 4.2.2 For each amount class, check isEqualTo().(ModellingMonetaryTest#testMonetaryAmount_isEqualTo)

[SUCCESS] 4.2.2 For each amount class, check isEqualTo(), regardless different MonetaryContext instances.(ModellingMonetaryTest#testMonetaryAmount_isEqualToRegardlessMonetaryContext)

[SUCCESS] 4.2.2 For each amount class, check isEqualTo(), regardless implementation type.(ModellingMonetaryTest#testMonetaryAmount_isEqualToRegardlessType)

[SUCCESS] 4.2.2 For each amount class, check isGreaterThan().(ModellingMonetaryTest#testMonetaryAmount_isGreaterThan)

[SUCCESS] 4.2.2 For each amount class, check isGreaterThanOrEquals().(ModellingMonetaryTest#testMonetaryAmount_isGreaterThanOrEquals)

[SUCCESS] 4.2.2 For each amount class, check isLessThan().(ModellingMonetaryTest#testMonetaryAmount_isLessThan)

[SUCCESS] 4.2.2 For each amount class, check isLessThanOrEqualTo().(ModellingMonetaryTest#testMonetaryAmount_isLessThanOrEqualTo)

[SUCCESS] 4.2.2 For each amount class, ensure multiplication with exceeding values throws ArithmeticException.(ModellingMonetaryTest#testMultiplyExceedsCapabilities)

[SUCCESS] 4.2.2 For each amount class, ensure multiplication of null throws NullPointerException.(ModellingMonetaryTest#testMultiplyNull)

[SUCCESS] 4.2.2 For each amount class, ensure multiplication by one returns same instance.(ModellingMonetaryTest#testMultiplyOne)

[SUCCESS] 4.2.2 For each amount class, ensure correct multiplication of decimal values.(ModellingMonetaryTest#testMultiply_Decimals)

[SUCCESS] 4.2.2 For each amount class, ensure correct multiplication of int values.(ModellingMonetaryTest#testMultiply_Integral)

[SUCCESS] 4.2.2 For each amount class, test negate().(ModellingMonetaryTest#testNegate)

[SUCCESS] 4.2.2 For each amount class, test query().(ModellingMonetaryTest#testQuery)

[SUCCESS] 4.2.2 For each amount class, test query(), MonetaryQuery throws exception, MonetaryException expected.(ModellingMonetaryTest#testQueryInvalidQuery)

[SUCCESS] 4.2.2 For each amount class, test query(null), NullPointerException expected.(ModellingMonetaryTest#testQueryNull)

[SUCCESS] 4.2.2 For each amount class, ensure correct results for remainder.(ModellingMonetaryTest#testRemainder)

[SUCCESS] 4.2.2 For each amount class, ensure remainder(null), throws NullPointerException.(ModellingMonetaryTest#testRemainderNull)

[SUCCESS] 4.2.2 For each amount class, ensure remainder(0), double, throws ArithmeticException.(ModellingMonetaryTest#testRemainderZero_Double)

[SUCCESS] 4.2.2 For each amount class, ensure remainder(0), long, throws ArithmeticException.(ModellingMonetaryTest#testRemainderZero_Long)

[SUCCESS] 4.2.2 For each amount class, ensure remainder(0), Number, throws ArithmeticException.(ModellingMonetaryTest#testRemainderZero_Number)

[SUCCESS] 4.2.2 For each amount class, ensure scaleByPowerOfTen(1) returns correct results.(ModellingMonetaryTest#testScaleByPowerOfTen)

[SUCCESS] 4.2.2 For each amount class, test signum().(ModellingMonetaryTest#testSignum)

[SUCCESS] 4.2.2 For each amount class, ensure correct subtraction of mixed fractions.(ModellingMonetaryTest#testSubtractMixedFractions)

[SUCCESS] 4.2.2 For each amount class, ensure correct subtraction of mixed ints.(ModellingMonetaryTest#testSubtractMixedIntegers)

[SUCCESS] 4.2.2 For each amount class, ensure correct subtraction of negative ints.(ModellingMonetaryTest#testSubtractNegativeIntegers)

[SUCCESS] 4.2.2 For each amount class, ensure correct subtraction of positive fractions.(ModellingMonetaryTest#testSubtractPositiveFractions)

[SUCCESS] 4.2.2 For each amount class, ensure correct subtraction of positive ints.(ModellingMonetaryTest#testSubtractPositiveIntegers)

[SUCCESS] 4.2.2 For each amount class, ensure subtraction with exceeding capabilities throws ArithmeticException.(ModellingMonetaryTest#testSubtract_ExceedsCapabilities)

[SUCCESS] 4.2.2 For each amount class, ensure subtraction with invalid currency throws MonetaryException.(ModellingMonetaryTest#testSubtract_IncompatibleCurrencies)

[SUCCESS] 4.2.2 For each amount class, ensure subtraction with null throws NullPointerException.(ModellingMonetaryTest#testSubtract_Null)

[SUCCESS] 4.2.2 For each amount class, ensure subtraction of 0 returns same instance.(ModellingMonetaryTest#testSubtract_Zero)

[SUCCESS] 4.2.2 For each amount class, test with().(ModellingMonetaryTest#testWith)

[SUCCESS] 4.2.2 For each amount class, test with().(ModellingMonetaryTest#testWith4ProvidedOperators)

[SUCCESS] 4.2.2 Bad case: For each amount class, test with(), operator throws exception.(ModellingMonetaryTest#testWithInvalidOperator)

[SUCCESS] 4.2.2 Bad case: For each amount class, test with(null), expected NullPointerException.(ModellingMonetaryTest#testWithNull)

[SUCCESS] 4.2.2 Bad case: For each amount class, test with(), operator throws exception.(ModellingMonetaryTest#testWithNull4ProvidedOperators)

[SUCCESS] 4.2.6 Ensure MonetaryAmountFactory instances are accessible for all amount types under test.(CreatingMonetaryTest#testAccessToMonetaryAmountFactory)

[SUCCESS] 4.2.6 Bad case: For each MonetaryAmount Factory: Create zero amounts from a factory with an invalid currency.(CreatingMonetaryTest#testMonetaryAmountFactoryCreateAmountsWithInvalidCurrency)

[SUCCESS] 4.2.6 Bad case: For each MonetaryAmount Factory: Create zero amounts from a

factory with an invalid
MonetaryContext.(CreatingMonetaryTest#testMonetaryAmountFactoryCreateAmountsWithInvalidMonetaryContext)
[SUCCESS] 4.2.6 Bad case: For each MonetaryAmount Factory: Create negative amounts, with no currency, expect
MonetaryException.(CreatingMonetaryTest#testMonetaryAmountFactoryCreateNegativeInvalidContext_BadCase)
[SUCCESS] 4.2.6 Bad case: For each MonetaryAmount Factory: Create negative amounts, with invalid currency, expect
MonetaryException.(CreatingMonetaryTest#testMonetaryAmountFactoryCreateNegativeInvalidCurrency_BadCase)
[SUCCESS] 4.2.6 Bad case: For each MonetaryAmount Factory: Create negative amounts, with no currency, expect
MonetaryException.(CreatingMonetaryTest#testMonetaryAmountFactoryCreateNegativeNoCurrency_BadCase)
[SUCCESS] 4.2.6 For each MonetaryAmount Factory: Create positive amounts.(CreatingMonetaryTest#testMonetaryAmountFactoryCreatePositiveAmountsWithCurrencies)
[SUCCESS] 4.2.6 For each MonetaryAmount Factory: Create positive amounts with explicit MonetaryContext.(CreatingMonetaryTest#testMonetaryAmountFactoryCreatePositiveAmountsWithContexts)
[SUCCESS] 4.2.6 For each MonetaryAmount Factory: Create positive amounts using doubles with explicit MonetaryContext (precision/scale).(CreatingMonetaryTest#testMonetaryAmountFactoryCreatePositiveAmountsWithContexts2)
[SUCCESS] 4.2.6 For each MonetaryAmount Factory: Create positive amounts using BigDecimal with explicit MonetaryContext (precision/scale).(CreatingMonetaryTest#testMonetaryAmountFactoryCreatePositiveAmountsWithContexts3)
[SUCCESS] 4.2.6 Bad case: For each MonetaryAmount Factory: Create positive amounts using invalid numbers, expecting ArithmeticException thrown.(CreatingMonetaryTest#testMonetaryAmountFactoryCreatePositiveAmountsWithInvalidNumber)
[SUCCESS] 4.2.6 Bad case: For each MonetaryAmount Factory: Create negative amounts with an invalid currency, expecting MonetaryException thrown.(CreatingMonetaryTest#testMonetaryAmountFactoryCreatePositiveInvalidContext_BadCase)
[SUCCESS] 4.2.6 Bad case: For each MonetaryAmount Factory: Create negative amounts with an invalid currency, expecting MonetaryException thrown.(CreatingMonetaryTest#testMonetaryAmountFactoryCreatePositiveInvalidCurrency_BadCase)
[SUCCESS] 4.2.6 Bad case: For each MonetaryAmount Factory: Create negative amounts without currency, expecting MonetaryException thrown.(CreatingMonetaryTest#testMonetaryAmountFactoryCreatePositiveNoCurrency_BadCase)
[SUCCESS] 4.2.6 Ensure MonetaryAmountFactory instances support creation of 0 amounts, with explicit
MonetaryContext.(CreatingMonetaryTest#testMonetaryAmountFactoryCreateZeroAmountsWithDiffContexts)

[SUCCESS] 4.2.6 Ensure MonetaryAmountFactory instances support creation of 0 amounts, with different explicit MonetaryContext.(CreatingMonetaryTest#testMonetaryAmountFactoryCreateZeroAmountsWithDiffContexts2)

[SUCCESS] 4.2.6 Ensure MonetaryAmountFactory instances support creation of 0 amounts, with different explicit MonetaryContext (precision, scale).(CreatingMonetaryTest#testMonetaryAmountFactoryCreateZeroAmountsWithDiffContexts3)

[SUCCESS] 4.2.6 Ensure MonetaryAmountFactory instances support creation of 0 amounts.(CreatingMonetaryTest#testMonetaryAmountFactoryCreateZeroAmountsWithDiffCurrencies)

[SUCCESS] 4.2.6 Ensure MonetaryAmountFactory instances accessible for all amount types under test return correct min/max MonetaryContext.(CreatingMonetaryTest#testMonetaryAmountFactoryMinMaxCapabilities)

[SUCCESS] 4.2.6 Ensure MonetaryAmountFactory instances accessible for all amount types under test return correct min/max MonetaryContext (min <= max).(CreatingMonetaryTest#testMonetaryAmountFactoryMinMaxCapabilities_Compare)

[SUCCESS] 4.2.6 For each MonetaryAmount Factory: Create negative amounts.(CreatingMonetaryTest#testMonetaryAmountFactoryNegativePositiveAmountsWithCurrencies)

[SUCCESS] 4.2.6 For each MonetaryAmount Factory: Create negative amounts, with explicit MonetaryContext.(CreatingMonetaryTest#testMonetaryAmountFactoryNegativePositiveAmountsWithContexts)

[SUCCESS] 4.2.6 For each MonetaryAmount Factory: Create negative amounts, with explicit MonetaryContext.(CreatingMonetaryTest#testMonetaryAmountFactoryNegativePositiveAmountsWithContexts2)

[SUCCESS] 4.2.6 For each MonetaryAmount Factory: Create negative amounts, with explicit MonetaryContext.(CreatingMonetaryTest#testMonetaryAmountFactoryNegativePositiveAmountsWithContexts3)

[SUCCESS] 4.2.6 Bad case: For each MonetaryAmount Factory: Create negative amounts, with invalid numeric value, expect ArithmeticException.(CreatingMonetaryTest#testMonetaryAmountFactoryNegativePositiveAmountsWithInvalidNumber)

[SUCCESS] 4.2.6 Ensure MonetaryAmountFactory instances accessible for all amount types under test return correct amount type.(CreatingMonetaryTest#testMonetaryAmountFactoryReturnsCorrectType)

[SUCCESS] 4.2.2 Checks if a correct Double value is returned, no truncation is allowed to be performed.(ExternalizingNumericValueTest#testDoubleNegative)

[SUCCESS] 4.2.3 Check if a correct double value is returned, truncation is allowed to be performed (but is not necessary).(ExternalizingNumericValueTest#testDoubleValueWithTruncationZero)

[SUCCESS] 4.2.3 Checks if a correct double value is returned, truncation is allowed to be performed.(ExternalizingNumericValueTest#testDoubleWithTruncationNegative)

[SUCCESS] 4.2.3 Checks if a correct Integer value is returned, no truncation is allowed to be performed.(ExternalizingNumericValueTest#testIntegerNegative)

[SUCCESS] 4.2.3 Check if a correct integer value is returned, truncation is allowed to be performed. Check should be done for every JDK type supported.(ExternalizingNumericValueTest#testIntegerValueWithTruncationZero)

[SUCCESS] 4.2.3 Check if a correct integer value is returned, truncation is allowed to be

performed..(ExternalizingNumericValueTest#testIntegerWithTruncationNegative)

[SUCCESS] 4.2.3 Check if a correct integer value is returned, no truncation is allowed to be performed.(ExternalizingNumericValueTest#testIntegerZero)

[SUCCESS] 4.2.3 Checks if a correct negative long value is returned, no truncation is allowed to be performed.(ExternalizingNumericValueTest#testLongNegative)

[SUCCESS] 4.2.3 Check if a correct long value is returned, truncation is allowed to be performed. Check should be done for every JDK type supported.(ExternalizingNumericValueTest#testLongValueWithTruncationZero)

[SUCCESS] 4.2.3 Checks if a correct long value is returned, truncation is allowed to be performed.(ExternalizingNumericValueTest#testLongWithTruncationNegative)

[SUCCESS] 4.2.3 Check if a correct long zero value is returned, no truncation is allowed to be performed.(ExternalizingNumericValueTest#testLongZero)

[SUCCESS] 4.2.3 Ensure NumberValue numberValue() works correnctly.(ExternalizingNumericValueTest#testNumberTypeNegative)

[SUCCESS] 4.2.3 Checks if number type is not null and returning a concrete (no abstract class or interface).(ExternalizingNumericValueTest#testNumberTypeZero)

[SUCCESS] 4.2.3 Checks if a correct long value is returned, truncation is allowed to be performed. Check should be done for every JDK type.(ExternalizingNumericValueTest#testNumberValueWithTruncationNegative)

[SUCCESS] 4.2.3 Checks if a correct double value is returned, truncation is allowed to be performed. Check should be done for every JDK type.(ExternalizingNumericValueTest#testNumberValueWithTruncationNegative_Double)

[SUCCESS] 4.2.3 Checks if a correct double value is returned, truncation is allowed to be performed. Check should be done for every JDK type.(ExternalizingNumericValueTest#testNumberValueWithTruncationNegative_Float)

[SUCCESS] 4.2.3 Checks if a correct int value is returned, truncation is allowed to be performed. Check should be done for every JDK type.(ExternalizingNumericValueTest#testNumberValueWithTruncationNegative_Integer)

[SUCCESS] 4.2.3 Checks if a correct Number value is returned, truncation is allowed to be performed. Check should be done for every JDK type.(ExternalizingNumericValueTest#testNumberValueWithTruncationNegative_Long)

[SUCCESS] 4.2.3 Checks if a correct double value is returned, truncation is allowed to be performed. Check should be done for every JDK type.(ExternalizingNumericValueTest#testNumberValueWithTruncationNegative_Short)

[SUCCESS] 4.2.3 Check if a correct Number value is returned, truncation is allowed to be performed. Check should be done for every JDK type supported.(ExternalizingNumericValueTest#testNumberValueWithTruncationZero)

[SUCCESS] 4.2.3 Check if a correct long zero value is returned, no truncation is allowed to be performed.(ExternalizingNumericValueTest#testNumberValueZero)

[SUCCESS] 4.2.3 Check if a correct number value is returned, truncation is allowed to be performed. Check should be done for every JDK type supported.(ExternalizingNumericValueTest#testNumberWithTruncationNegative)

[SUCCESS] 4.2.3 Test correct precision values, including border cases.(ExternalizingNumericValueTest#testPrecisionNegative)

[SUCCESS] 4.2.3 Ensure NumberValue getPrecision() works correctly.(ExternalizingNumericValueTest#testPrecisionValues)

[SUCCESS] 4.2.3 Check if a correct precision value is returned. Check should be done for every JDK type supported.(ExternalizingNumericValueTest#testPrecisionZero)

[SUCCESS] 4.2.3 Amount types do not return a NumberValue of null.(ExternalizingNumericValueTest#testReturningNumberValueIsNotNull)

[SUCCESS] 4.2.3 Test correct scale values, including border cases.(ExternalizingNumericValueTest#testScaleNegative)

[SUCCESS] 4.2.3 Ensure NumberValue getScale() works correctly.(ExternalizingNumericValueTest#testScaleValues)

[SUCCESS] 4.2.3 Check if a correct scale value is returned. Check should be done for every JDK type supported.(ExternalizingNumericValueTest#testScaleZero)

[SUCCESS] 4.2.3 Ensure NumberValue doubleValue(), doubleValueExact() provide correct values.(ExternalizingNumericValueTest#testValidDouble)

[SUCCESS] 4.2.3 Ensure NumberValue doubleValue() is truncated.(ExternalizingNumericValueTest#testValidDoubleWithTruncation)

[SUCCESS] 4.2.3 Ensure NumberValue intValue(), intValueExact() provide correct values.(ExternalizingNumericValueTest#testValidInteger)

[SUCCESS] 4.2.3 Ensure NumberValue intValue() is truncated.(ExternalizingNumericValueTest#testValidIntegerWithTruncation)

[SUCCESS] 4.2.3 Ensure NumberValue longValue(), longValueExact() provide correct values.(ExternalizingNumericValueTest#testValidLong)

[SUCCESS] 4.2.3 Ensure NumberValue longValue() is truncated.(ExternalizingNumericValueTest#testValidLongWithTruncation)

[SUCCESS] 4.2.3 Ensure NumberValue asType(BigDecimal.class) provides correct values.(ExternalizingNumericValueTest#testValidNumberBD)

[SUCCESS] 4.2.3 Ensure NumberValue asType(BigInteger.class) provides correct values.(ExternalizingNumericValueTest#testValidNumberBI)

[SUCCESS] 4.2.3 Ensure NumberValue byteValue() is truncated.(ExternalizingNumericValueTest#testValidNumberWithTruncation_Byte)

[SUCCESS] 4.2.3 Ensure NumberValue doubleValue() is truncated.(ExternalizingNumericValueTest#testValidNumberWithTruncation_Double)

[SUCCESS] 4.2.3 Ensure NumberValue floatValue() is truncated.(ExternalizingNumericValueTest#testValidNumberWithTruncation_Float)

[SUCCESS] 4.2.3 Ensure NumberValue intValue() is truncated correctly.(ExternalizingNumericValueTest#testValidNumberWithTruncation_Integer)

[SUCCESS] 4.2.3 Ensure NumberValue shortValue() is truncated.(ExternalizingNumericValueTest#testValidNumberWithTruncation_Short)

[SUCCESS] 4.2.4 Ensures the result of all operators under test is of the same class as the input.(FunctionalExtensionPointsTest#testOperatorReturnTypeEqualsParameter)

[SUCCESS] 4.2.7 Access named roundings and ensure TCK named roundings are registered.(AccessingCurrenciesAmountsRoundingsTest#testAccessCustomRoundings)

[SUCCESS] 4.2.7 Ensure Monetary instances are available, for all registered currencies.(AccessingCurrenciesAmountsRoundingsTest#testAccessRoundingsForCustomCurrencies_Default)

[SUCCESS] 4.2.7 Ensure Monetary instances are available, also for any custom currency (not registered).(AccessingCurrenciesAmountsRoundingsTest#testAccessRoundingsForCustomCurrencies_Explicit)

[SUCCESS] 4.2.7 Expected NullPointerException accessing a rounding with 'Monetary.getRounding(null)'.(AccessingCurrenciesAmountsRoundingsTest#testAccessRoundingsForCustomCurrencies_Explicit_Null)

[SUCCESS] 4.2.7 Ensure NullPointerException is thrown for 'Monetary.getRounding((RoundingContext) null)'.(AccessingCurrenciesAmountsRoundingsTest#testAccessRoundingsWithMonetaryContext_Null)

[SUCCESS] 4.2.7 Ensure correct MonetaryRounding returned for a mathematical RoundingQuery.(AccessingCurrenciesAmountsRoundingsTest#testAccessRoundingsWithRoundingContext)

[SUCCESS] 4.2.7 Test if Monetary provides all ISO related entries similar to java.util.Currency.(AccessingCurrenciesAmountsRoundingsTest#testAllISOCurrenciesAvailable)

[SUCCESS] 4.2.7 Test if Monetary provides all locale related entries similar to java.util.Currency.(AccessingCurrenciesAmountsRoundingsTest#testAllLocaleCurrenciesAvailable)

[SUCCESS] 4.2.7 Ensure a default MonetaryAmountFactory is available.(AccessingCurrenciesAmountsRoundingsTest#testAmountDefaultType)

[SUCCESS] 4.2.7 Ensure correct query function, Monetary.getAmountFactories should return factoryfor explicit acquired amount types.(AccessingCurrenciesAmountsRoundingsTest#testAmountQueryType)

[SUCCESS] 4.2.7 Ensure amount factories are accessible for all types available in Monetary.(AccessingCurrenciesAmountsRoundingsTest#testAmountTypesInstantiatable)

[SUCCESS] 4.2.7 Ensure amount classes to test are setup and registered/available in Monetary.(AccessingCurrenciesAmountsRoundingsTest#testAmountTypesProvided)

[SUCCESS] 4.2.7 Test if Monetary provides correct ISO related entries similar to java.util.Currency.(AccessingCurrenciesAmountsRoundingsTest#testCorrectISOCodes)

[SUCCESS] 4.2.7 Test if Monetary provides correct locale related entries similar to java.util.Currency.(AccessingCurrenciesAmountsRoundingsTest#testCorrectLocales)

[SUCCESS] 4.2.7 Test if Monetary provides customized locale identified currencies.(AccessingCurrenciesAmountsRoundingsTest#testCustomCurrencies)

[SUCCESS] 4.2.7 Access custom roundings and ensure correct functionality.(AccessingCurrenciesAmountsRoundingsTest#testCustomRoundings)

[SUCCESS] 4.2.7 Ensure MonetaryException is thrown for accessing invalid named rounding.(AccessingCurrenciesAmountsRoundingsTest#testCustomRoundings_Foo)

[SUCCESS] 4.2.7 Ensure NullPointerException is thrown for Monetary.getRounding((String) null).(AccessingCurrenciesAmountsRoundingsTest#testCustomRoundings_Null)

[SUCCESS] 4.3.1 Access Conversion to term currency code XXX for all providers that support according conversion, ifavailable a non-null CurrencyConversion must be provided.(MonetaryConversionsTest#testConversionsAreAvailable)

[SUCCESS] 4.3.1 Access Conversion by query to term currency XXX for all providers that support according conversion, ifavailable a non-null CurrencyConversion must be provided.(MonetaryConversionsTest#testConversionsAreAvailableWithQuery)

[SUCCESS] 4.3.1 Access and test the default conversion provider chain.(MonetaryConversionsTest#testDefaultProviderChainIsDefined)

[SUCCESS] 4.3.1 Access and test the default conversion provider chain, by accessing a defaultCurrencyConversion for term CurrencyUnit CHF.(MonetaryConversionsTest#testDefaultProviderChainIsDefinedDefault)

[SUCCESS] 4.3.1 Access and test the default conversion provider chain, by accessing a defaultCurrencyConversion for term currency code CHF.(MonetaryConversionsTest#testDefaultProviderChainIsDefinedDefault2)

[SUCCESS] 4.3.1 Access and test the default conversion provider chain, by accessing a defaultCurrencyConversion for
ConversionQuery.(MonetaryConversionsTest#testDefaultProviderChainIsDefinedDefaultWithContext)

[SUCCESS] 4.3.1 Test if all ExchangeRateProvider instances returns valid ProviderContext.(MonetaryConversionsTest#testProviderMetadata)

[SUCCESS] 4.3.1 Test if all CurrencyConversion instances returns valid ConversionContext, accessed by currency code.(MonetaryConversionsTest#testProviderMetadata2)

[SUCCESS] 4.3.1 Test if all CurrencyConversion instances returns valid ConversionContext, accessed by ConversionQuery/currency code.(MonetaryConversionsTest#testProviderMetadata2WithContext)

[SUCCESS] 4.3.1 Test if all CurrencyConversion instances returns valid ConversionContext, accessed by CurrencyUnit.(MonetaryConversionsTest#testProviderMetadata3)

[SUCCESS] 4.3.1 Test if all CurrencyConversion instances returns valid ConversionContext, accessed by
ConversionQuery/CurrencyUnit.(MonetaryConversionsTest#testProviderMetadata3WithContext)

[SUCCESS] 4.3.1 Ensure at least one conversion provider is available, TestRateProvider must be present.(MonetaryConversionsTest#testProvidersAvailable)

[SUCCESS] 4.3.1 Bad case: Access invalid ExchangeRateProvider, expect MonetaryException thrown, using default provider chain.(MonetaryConversionsTest#testUseInvalidProvider)

[SUCCESS] 4.3.1 Bad case: Access invalid ExchangeRateProvider, expect MonetaryException thrown, using explicit
provider.(MonetaryConversionsTest#testUseInvalidProviderWithinChain)

[SUCCESS] 4.3.3 Test access of Conversion Rates, using TCK provided rate
provider.(ExchangeRatesAndRateProvidersTest#testAccessKnownRates)

[SUCCESS] 4.3.3 Test access to exchange rates from TestRateProvider, using target CurrencyUnit.(ExchangeRatesAndRateProvidersTest#testAccessKnownRatesAndContext)

[SUCCESS] 4.3.3 Test access to exchange rates from TestRateProvider, using target currency code.(ExchangeRatesAndRateProvidersTest#testAccessKnownRatesWithCodes)

[SUCCESS] 4.3.3 Test access to conversion rates, including known factor, using TestRateProvider.(ExchangeRatesAndRateProvidersTest#testAccessKnownRatesWithCodesAndContext)

[SUCCESS] 4.3.3 Test access to conversion rate for currency codes, using default
provider.(ExchangeRatesAndRateProvidersTest#testAccessRates_IdentityRatesWithCodes)

[SUCCESS] 4.3.3 Test access to identity conversion rate for CurrencyUnits, using default
provider.(ExchangeRatesAndRateProvidersTest#testAccessRates_IdentityRatesWithUnits)

[SUCCESS] 4.3.3 Test access to conversion rate for CurrencyQuery, using default
provider.(ExchangeRatesAndRateProvidersTest#testAccessRates_IdentityRatesWithUnitsAndContext)

[SUCCESS] 4.3.3 Bad case: try accessing exchange rates with invalid base currency
code.(ExchangeRatesAndRateProvidersTest#testInvalidUsage_InvalidSourceCurrency)

[SUCCESS] 4.3.3 Bad case: try accessing exchange rates with null
ConversionQuery.(ExchangeRatesAndRateProvidersTest#testInvalidUsage_InvalidSourceCurrency
AndContext)

[SUCCESS] 4.3.3 Bad case: try accessing exchange rates with invalid term currency
code.(ExchangeRatesAndRateProvidersTest#testInvalidUsage_InvalidTargetCurrency)

[SUCCESS] 4.3.3 Bad case: try accessing exchange rates with null base currency
code.(ExchangeRatesAndRateProvidersTest#testInvalidUsage_NullSourceCurrency)

[SUCCESS] 4.3.3 Bad case: try accessing exchange rates with null base CurrencyUnit.(ExchangeRatesAndRateProvidersTest#testInvalidUsage_NullSourceCurrencyUnit)

[SUCCESS] 4.3.3 Bad case: try accessing exchange rates with null term currency code.(ExchangeRatesAndRateProvidersTest#testInvalidUsage_NullTargetCurrency)

[SUCCESS] 4.3.3 Bad case: try accessing exchange rates with null term CurrencyUnit.(ExchangeRatesAndRateProvidersTest#testInvalidUsage_NullTargetCurrencyUnit)

[SUCCESS] 4.3.3 Ensure additional ConversionQuery data is passed correctly to SPIs.(ExchangeRatesAndRateProvidersTest#testPassingOverConversionContextToSPIs)

[SUCCESS] 4.3.2 Test successful conversion for CHF -> F00, using TestRateProvider.(ConvertingAmountsTest#testConversion)

[SUCCESS] 4.3.2 Test correct ExchangeRate is returned for CHF -> F00, using TestRateProvider.(ConvertingAmountsTest#testConversionComparedWithRate)

[SUCCESS] 4.3.2 Bad case: Access CurrencyConversion with a CurrencyUnit==null, ensure NullPointerException is thrown.(ConvertingAmountsTest#testNullConversion1)

[SUCCESS] 4.3.2 Bad case: Access CurrencyConversion with a currency code==null, ensure NullPointerException is thrown.(ConvertingAmountsTest#testNullConversion2)

[SUCCESS] 4.3.2 Bad case: Try CurrencyConversion to an inconvertible (custom) currency (FOOANY), ensure CurrencyConversionException is thrown.(ConvertingAmountsTest#testUnsupportedConversion)

[SUCCESS] 4.3.4 Test correct rate evaluation for different conversion provider chains, with historic rates.(ProviderChainsTest#testCorrectRateEvaluationInChainHistoric)

[SUCCESS] 4.3.4 Test correct rate evaluation for different conversion provider chains.(ProviderChainsTest#testCorrectRateEvaluationInChain_diffProviders)

[SUCCESS] 4.3.4 Test correct rate evaluation for different conversion provider chains, with duplicate provider entries.(ProviderChainsTest#testCorrectRateEvaluationInChain_sameProviders)

[SUCCESS] 4.3.4 Test availability of TCK provided providers.(ProviderChainsTest#testTCKRateChainAvailability)

[SUCCESS] 4.4.1 Ensures for each locale defined by DecimalFormat.getAvailableLocales() a MonetaryFormats.getAmountFormat(AmountFormatQuery) returns a formatter.(FormattingMonetaryTest#testAmountStyleOf)

[SUCCESS] 4.4.1 Formats amounts using all available locales.(FormattingMonetaryTest#testFormattingIsIndependentOfImplementation)

[SUCCESS] 4.4.1 Ensures for each locale defined by DecimalFormat.getAvailableLocales() a MonetaryAmountFormat instance is provided.(FormattingMonetaryTest#testGetAmountFormat)

[SUCCESS] 4.4.1 Ensures for each locale defined by DecimalFormat.getAvailableLocales() a MonetaryFormats.isAvailable(Locale) is true.(FormattingMonetaryTest#testGetAvailableLocales)

[SUCCESS] 4.4.1 Ensures all Locales defined by DecimalFormat.getAvailableLocales() are available for monetary formatting.(FormattingMonetaryTest#testLocalesSupported)

[SUCCESS] 4.4.1 Ensures the system.s default locale is supported for MonetaryAmountFormat.(FormattingMonetaryTest#testNoDepOnAmountImplementation)

[SUCCESS] 4.4.1 Test formats and parses (round-trip) any supported amount type for each supported Locale, using different format queries.(FormattingMonetaryTest#testParseDifferentStyles)

[SUCCESS] 4.4.1 Test formats and parses (round-trip) any supported amount type for each supported Locale.(FormattingMonetaryTest#testParseIsIndependentOfImplementation)

[SUCCESS] 4.4.1 Test formats and parses (round-trip) any supported amount type for each

```
supported Locale, checks results for different
currencies(FormattingMonetaryTest#testParseWithDifferentCurrencies)
```

```
JSR 354 TCK, version 1.0 Summary
```

```
-----

TOTAL TESTS EXECUTED : 221
TOTAL TESTS SKIPPED  : 0
TOTAL TESTS SUCCESS  : 221
TOTAL TESTS FAILED   : 0
```

```
-- JSR 354 TCK finished --
```

```
=====
Custom suite
Total tests run: 1, Failures: 0, Skips: 0
=====
```

```
Process finished with exit code 0
```

2.2. Contacts

Basically you can use the JSR's public mailing list to get in contact or write an email to the JSR's [spec lead](#).

If you have improvements or fixes, create a pull request on GitHub.